

Notes:

- 1) Installation according to installation instructions.
- 2) All dimensions in [mm].
- 3) Stated criteria has been considered as a minimum recommendation. In the event of a lack of upstream sand traps or a high sand/sludge content, the distance should be increased.
- 4) Any accessories are not shown in the drawing.



Min. manhole's diameter recommended:
D-1000 mm.

Minimum mounting opening:
Dm = Ø400mm

Minimum recommended socket length: lmin = 110 mm

Parts lists:

A	1 pc	Vortex valve housing	PUR
B	7 pcs	Locking bolts	316
C	1 pc	Outlet	PUR

 Datasheet			
Product nr: VSU6DN25-04		Product name: Vortex valve FluidVertic Standard, VSU6DN025, PUR, outlet 110 PVC spigot	
NRF no: 3024184			
Version: 30-10-2024	Page: 1 of 1	Performance: 0.4 l/s at 1.2m pressure head	
 Pionerer i regnvannshåndtering		<small>Copyright This drawing is protected intellectual property ownership bu Norwegian law and may not be unjustifiably copied, used or sent to third parties without MFT's approval. The subscription must also not be used on a tender basis without MFT's permission. The knowledge our customers acquire during project preparation, ordering, purchasing, assembly, etc. The customer cannot utilize themself on his own, through later own construction of plagiarism etc. Violation of these obligations can result in both criminal and liability.</small>	
			mft.no