











Notes:

1) Installation according to the installation instructions
2) All dimensions in [mm]
3) Dimensions given are minimum. Without an upstream sand trap, or with a high sand/sludge content, the distance should be increased.
4) Any accessories are not shown on the drawing.

Min. recommended manhole diameter:
D-1000mm.

Min. installation opening, Dm:
Ø500mm

Min. recommended stub length, l_{min}: 110mm

Parts list:

A	1 pcs	Vortex housing	PUR
B	17 pcs	Locking bolts	316
C	1 pcs	Outlet	PUR

Capacity guarantee:
+/- 5% for flow rate at hb=1.2m

Datasheet

Product no.:
STD6DN50-17

Product name:
Vortex valve FluidVertic Standard, VSU6DN050, PUR, outlet 110 PVC spigot

NRF no.:
3024177

Version:
30-10-2026

Page:
1 of 1

Performance:
1.7 l/s at 1.2m head

MFT
Pionerer i regnvannshåndtering

Copyright
This drawing is protected by Norwegian copyright law and must not be copied, used or passed on to third parties without MFT's approval. Nor may the drawing be used as a basis for tenders without MFT's permission. Knowledge acquired by our customers during project preparation, ordering, purchase, installation etc. may not be exploited by the customer on their own, e.g. through later construction of copies. Breach of these obligations may result in both criminal and civil liability.

mft.no