

Pionerer i regnvannshåndtering

Suggested dimensioning range

Anmerkninger:

- 1) Installation according to installation instructions.
- 2) All dimensions in [mm].
- Stated criteria has been considered as a minimum recommendation. In the event of a lack of upstream sand traps or a high sand/sludge content, the distance should be increased.
- 4) Any accessories are not shown in the drawing.

Min. manhole's diameter recommended: ø1200mm.

Minimum mounting opening: DM_{min}: ø650mm

Parts list:

Α		Vortex valve housing	PUR
В	12 stk	Locking bolts	316
С	1 stk	Outlet	PUR

Accessories:

D	1 stk	Mouting plate	PUR
Е	1 stk	Gasket	Celleplast
F	8 stk	Eks bolts	316
G	1 stk	Filling piece	PE

Customized product dimensioning criteria

Dim. Water flow Qb (I/s): ___

Dim. Head pressure hb (m):


Outlet mounted against standard socket comes as standard option

Accessories:

construction of plagiarism etc. Violation of these obligations can result in both criminal

Mounting plate (Yes/No): _____

Filling piece for mounting plate customized to a manhole's diameter Dk (m): _____



Datasheet Product nr: Product name: VSU4DN125P-250 Vortex valve FluidVertic VSU VSU4DN125P-250, PUR, CUSTOMIZED NRF nr: Side: Version: Outlet's dmension: D-250 outlet (dim 250 PVC tip) 1 av 1 22-06-2021 This drawing is protected intellectual property ownership bu Norwegian law and may not be unjustifiably copied, used or sent to third parties without MFT's approval. The subscription must also not be used on a tender basis without MFT's permission. The knowledge our customers acquire during project preparation, ordering, purchasing, assembly, etc. The customer cannot utilize themself on his own, through later own

and liability.